





## Delta Plus MOBILE II

### A GSM/GPRS Telemetry Modem

Allows use of the mobile telephone network for Automatic Meter Reading (AMR), utility data collection and remote logging applications.

- **EASY TO INTERFACE TO YOUR EQUIPMENT....**
- **INTERCHANGEABLE WITH FIXED LINE MODEMS...**
- **REDUCED CONFIGURATION AND MAINTENANCE COSTS....**
- **IDEAL FOR USE IN THE UTILITY, VENDING AND SECURITY MARKETS....**
- Modem compatible communications data rates up to 9600bps
- Error correction including V110 (for ISDN/GSM connected Host)
- Always on GPRS capability as standard
- Industry standard 25 way D-type socket interface
- Advanced Super Caps allow no battery operation (Std Product)
- Flexible power supply of 6V to 14VDC
- Standby mode with current drain of < 50mW
- Typical average operating power of < 500mW
- Plug in compatibility with other Delta Plus and many other modems
- Local or remote antenna
- Dimensionally compact and cost effective



### ASL Holdings Ltd.

The Oaks, Spring Hill Office Park, Spring Hill Farm, Harborough Road, Pitsford, Northampton, NN6 9AA  
 Tel: 01604 883 880 Fax: 01604 883 881; email: sales@aslholdings.co.uk; web: <http://www.aslholdings.co.uk>

# Delta Plus MOBILE II

A second generation high speed telemetry modem for use on public mobile telephone networks. Ideal for Automatic Meter Reading and general low power telemetry applications.

The Delta Plus Mobile II is a new member of ASLH's well established and proven range of Delta Plus telemetry modems.

The Delta Plus Mobile II allows access to remote data via the public mobile telephone networks. The industry standard data port allows the unit to be connected to equipment in place of a fixed line modem. The flexible input power supply requirements further enhance the ease of use.

Whilst the replacement of batteries in consumer GSM phones is reluctantly accepted, it is not economic in many industrial applications due to problems of access and cost. This makes low operating power vital.

The Delta Plus Mobile II has been designed with that requirement paramount. Full power is only used when online. In low power standby mode it will still action commands from the host e.g. to dial or to answer a call.

In standby mode, at 6V the Delta Plus Mobile II consumes <50mW rising to a maximum of 0.5W when communicating. This allows the use of advanced Super Cap technology to eliminate the need for batteries and their associated problems.

For maximum compatibility and ease of use the unit has been designed to operate like a normal modem. There is no need to

understand additional GSM network specific operations.

Even when operating in GPRS mode, once installed, it acts like a leased line modem.

To reduce transmission times, the Delta Plus Mobile II can be used in V110 mode making and receiving calls to and from hosts connected using ISDN or GSM rather than standard telephone modems.

A suitable antenna can be fitted to the unit's flying lead or mounted remotely via an extension cable if required.

Installation is further simplified, as the unit is so light that it can be mounted via its 25 way 'D' connector.

Naturally, the Delta Plus Mobile II includes watchdog and power brown out detection to maximize high reliability of operation.

The Delta Plus Mobile II is ideal for use with electronic electricity meters where it is small enough to fit under the terminal cover.

Alternately the unit can be used for data logging applications where the low standby current requirements will allow a long battery life.



## Specification

Data rates & standards	V22 (1200bps), V22bis (2400bps), V32 (9600bps) . - [ V32bis (14,400bps) battery version only]
GPRS Protocol	Supports TCP/IP stack Class 10 and ASL high efficiency telemetry protocols (ATP)
Network compatibility	Quad band for use on GSM and GPRS (Class B 4+1) networks at 850/900/1800/1900MHz
SIM card	Secure mounting with easy access 'push - push' style SIM holder
Error Correction/ Data Compression	V42, V42bis standards for modem and V110 for ISDN and GSM hosted applications
Power supply	Powered from the host data port. +6V to +14 V dc Delta Plus Mobile II with Super Caps and no battery: 50mW standby, 500mW communicating - ASLH306. Delta Plus Mobile II with Super Caps and a lithium Ion battery: 30mW standby, 1W communicating - ASLH306BATT
Enclosure	Custom moulded plastic housing, size - 61x57x24mm.
Weight	70g
Environmental conditions	-20 to +55°C operating; -20 to +70°C storage. Humidity 0-95% non-condensing
Control of functions	By 'AT' compatible command subset
Auto dial/answer	Under 'AT' command control. Auto answer with Call Indicate
Antenna connector	SMA bulkhead connector on 130mm flying lead
Data port	RS232 (V24/28) asynchronous serial port supporting RXD, TXD, DCD, DTR, RTS and CTS
Data port connector	Integral 25 way 'D' socket. Standard pinout with power on pin 7 - ve, pin 9 and 15 + ve
Remote configuration	By the use of Hyper Terminal or any suitable terminal emulation package for access
Approvals	The product conforms to : 3GPP TS 51.010-1, EN60950, R&TTE directive 99/5/EC EMC Directive 89/336/EEC & Low Voltage Directive 73/23/EEC
Additional services	For more communications options see the separate data sheets for the other communications modules that are in the Delta Plus family. ASLH is also able to offer modems with customized configurations, tailored to specific customer's requirements as well as fully custom communications products. Please enquire for full details.

ASLH's policy is to upgrade and improve its products. The right is reserved to change these specifications without notice.

ASLH306 March/08

## ASL Holdings Ltd.

The Oaks, Spring Hill Office Park, Spring Hill Farm, Harborough Road, Pitsford, Northampton, NN6 9AA  
Tel: 01604 883 880 Fax: 01604 883 881; email: sales@aslholdings.co.uk; web: <http://www.aslholdings.co.uk>